



## P50 Marine Corrosion Free Foam Fire Extinguisher

### Product Description

The foam fire extinguisher has excellent firefighting capabilities making it effective on Class A materials fuelled by wood, paper and textiles as well as Class B fires fuelled by paints, solvents, oils and petrochemical products.

The extinguisher has also passed the EN3 test for use on live electrical equipment up to 1000V at a distance of 1mtr. The operational temperature range is from +5°C to +60°C

### Features

- Manufactured in Great Britain
- 10 year quality guarantee against material defects and workmanship
- Lightweight for easy of operation
- Requires only a yearly in-house compliance inspection using gauge check with magnet
- Composite material gives a corrosion free product
- Frost protection to -5°C is available
- 100% recyclable
- 100% UV protected
- Kitemarked approved
- MED approved



### Technical Specification

Model	Capacity (kg)	Fire Rating	Full Weight (kgs)	Temp Range	Operating Pressure (Bar) @ 20°C	Discharge Duration (Secs)	Discharge Range (mtr)	Diameter (mm)	Height (mm)
P50F6M	6	27A/183B	8.5	+5° to +60°C	12	40	4+	178	570
P50F9M	9	34A/233B	11.7	+5° to +60°C	12	49	7+	210	640

FlameSkill Ltd  
 1 Morton Peto Estate  
 Great Yarmouth  
 Norfolk  
 NR31 0LT  
 Tel: 01493 440464  
 Email: [admin@flameskill.co.uk](mailto:admin@flameskill.co.uk)  
 Web: [www.flameskill.co.uk](http://www.flameskill.co.uk)