



P50 Marine Corrosion Free Powder Fire Extinguisher

Product Description

ABC 40 powder is a combination of Mono-ammonium phosphate and ammonium sulphate.

On Class A fires the particles fuse and swell to form a barrier which excludes oxygen and prevents re-ignition. On Class B fires, the powder interferes with the chemical reactions, thus the flame ceases to exist.

The powder is non-conductive.

ABC 40 powder with extinguisher Class A (carbonaceous) fires, Class B (flammable liquid) fires and Class C (flammable gas) fires.

Features

- Manufactured in Great Britain
- 10 year quality guarantee against material defects and workmanship
- Lightweight for easy of operation
- Requires only a yearly in-house compliance inspection using gauge check with magnet
- Composite material gives a corrosion free product
- 100% recyclable
- 100% UV protected
- Kitemarked approved
- MED approved



Technical Specification

Model	Capacity (kg)	Fire Rating	Full Weight (kgs)	Temp Range	Operating Pressure (Bar) @ 20°C	Discharge Duration (Secs)	Discharge Range (mtr)	Diameter (mm)	Height (mm)
P50P6M	6	34A/183B	8.5	-20° to +60°C	12	20	5+	178	570
P50P9M	9	43A/233B	11.7	-20° to +60°C	12	22	7+	210	640

FlameSkill Ltd
1 Morton Peto Estate
Great Yarmouth
Norfolk
NR31 0LT
Tel: 01493 440464
Email: admin@flameskill.co.uk
Web: www.flameskill.co.uk