



Helping to protect lives globally

JoBird®

BUILT BY THE BEST TO
WITHSTAND THE WORST.

Product data sheet

JB08H Fire Hose Cabinet



Typical use:

For the storage of 4 x 30M fire hoses, 2 x water nozzles and 1 x foam branch. This cabinet is widely used in the Offshore energy and marine sectors.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The cabinet comes fitted with 2 x 316SS hose pins to hold the hoses, 1 x 316SS double nozzle brackets for the water nozzles and 1 x 316SS single bracket for the foam branch.

The door can be specified with left or right hinging and features a nylon rod handle to pull the door open to guarantee fast access even when wearing gloves.

Standard specification:

Dimensions (mm)

Height x width x depth: 1474 x 918 x 477

Aperture: 1234H x 704W

Internal depth: 388

Weight Kg: 35Kg

Material specification:

Colour: Red RAL 3000

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: 316 Stainless steel

Handle: Nylon Rod

Seal: EPDM

Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window with bezel

316 Stainless steel 3 way locking

Double doors

Manufactured in the UK

