



Helping to protect lives globally

JoBird®

BUILT BY THE BEST TO  
WITHSTAND THE WORST.

## Product data sheet

# JB16R 20m Hydrant Cabinet

### Typical use:

For the storage of 1 x 20m firehose and nozzle. This cabinet is widely used in the Offshore energy and marine sectors.

### Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The door can be specified with left or right hinging and features a rotary graphite nylon handle to pull the door open to guarantee fast access even when wearing gloves.

### Standard specification:

Dimensions (mm)

Height x width x depth: 630 x 716 x 216

Aperture: 460H x 520W

Internal depth: 144

Weight Kg: 8Kg

### Material specification:

Colour: Red RAL3000

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: 316 Stainless steel

Handle: Nylon Graphite Rotary with Biomaster® anti-microbial technology and anti-tamper facility

Seal: EPDM



### Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window with bezel

Manufactured in the UK

