



Helping to protect lives globally

Jo**Bird**[®]

BUILT BY **THE BEST** TO
WITHSTAND **THE WORST.**

Product data sheet

JB80 Fire Hose Cabinet (10-20m)



Typical use:

For the storage of 1 x 10- 20m firehose and nozzle. This cabinet is widely used in the Offshore energy and marine sectors.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 66. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The door can be specified with left or right hinging and features a rotary graphite nylon handle with anti-microbial additive which can be fitted with an anti-tamper seal. The large yellow handle is easy to rotate to open the door and guarantee fast access even when wearing gloves.

Standard specification:

Dimensions (mm)

Height x width x depth: 524 x 561 x 198

Aperture: 374H x 414W

Internal depth: 162

Weight Kg: 6.1Kg

Material specification:

Colour: Red RAL3000

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: 316 Stainless steel

Handle: Nylon Graphite Rotary/316 Stainless steel with anti-microbial additive.

Seal: EPDM

Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window

Manufactured in the UK

