



Helping to protect lives globally

Jo**Bird**®

BUILT BY **THE BEST** TO
WITHSTAND **THE WORST.**

Product **data sheet**

JB02R Descent device cabinet



Typical use:

For the storage of approximately 12 emergency descent devices. Designed for use on offshore platforms and cruise ships. It is widely used by the world's top energy companies due to its durability.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for the descent devices in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The door can be specified with left or right hinging and features a graphite nylon/316 rotary handle to guarantee fast access in an emergency even when wearing gloves. The handle can be fitted with an anti-tamper seal.

Comes fitted with a central shelf as standard

Standard specification:

Dimensions (mm)

Height x width x depth: 937 x 835 x 347

Aperture: 755H x 630W

Internal depth: 275

Weight Kg: 15Kg

Material specification:

Colour: Green RAL 6029

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: 316 Stainless steel

Handle: Nylon / 316 Stainless steel with Biomaster® anti-microbial technology and anti-tamper facility

Seal: EPDM

Optional Extras:

Other RAL colours

Additional shelves

Class 1 fire retardant composites

Perspex window

Heating

Manufactured in the UK

