



Helping to protect lives globally

Jo**Bird**®

BUILT BY **THE BEST** TO
WITHSTAND **THE WORST.**

Product **data sheet**

JB10.600 Descent Devices Cabinet



Typical use:

For the storage of up to 30 x Descent Devices. This cabinet is widely used in the Offshore energy and marine sectors.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

This cabinet comes fitted with 2 shelves.

The door can be specified with left or right hinging and features a nylon rod handle to pull the door open to guarantee fast access even when wearing gloves.

Standard specification:

Dimensions (mm)

Height x width x depth: 1308 x 790 x 629

Aperture: 1084H x 586W

Internal depth: 549

Weight Kg: 24Kg

Material specification:

Colour: Green RAL6029

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: 316 Stainless steel

Handle: Nylon Rod

Seal: EPDM

Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window with bezel



Manufactured in the UK

