



Helping to protect lives globally

Jo**Bird**[®]

BUILT BY **THE BEST** TO
WITHSTAND **THE WORST.**

Product **data sheet**

JB13.460 General purpose cabinet



Typical use:

For the storage of miscellaneous equipment. Designed for use on and offshore. It is widely used by the world's top energy companies due to its durability.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The door can be specified with left or right hinging and features a nylon rod handle to pull the door open to guarantee fast access in an emergency even when wearing gloves.

Standard specification:

Dimensions (mm)

Height x width x depth: 942 x 572 x 483

Aperture: 757H x 365W

Internal depth: 410

Weight Kg: 12Kg

Material specification:

Colour: Green RAL 6029

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: 316 Stainless steel

Handle: Nylon Rod

Seal: EPDM

Optional Extras:

Other RAL colours

Shelf

Class 1 fire retardant composites

Perspex window

Heating



Manufactured in the UK

