



Helping to protect lives globally

JoBird®

BUILT BY THE BEST TO
WITHSTAND THE WORST.

Product data sheet

JB38 Stretcher Cabinet



Typical use:

For the storage of a basket type stretcher. This cabinet is widely used in the Offshore energy and marine sectors.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The door can be specified with left or right hinging and features a Stainless Steel 'L' handle to pull the door open to guarantee fast access even when wearing gloves.

Standard specification:

Dimensions (mm)

Height x width x depth: 2350 x 820 x 282

Aperture: 2175H x 615W

Internal depth: 220

Weight Kg: 32Kg

Material specification:

Colour: Green RAL 6029

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: Stainless Steel

Handle: Stainless Steel 'L' handle

Seal: EPDM

Optional Extras:


Other RAL colours

Class 1 fire retardant composites

Perspex window with bezel

316 Stainless steel 3 way locking

Double doors



Manufactured in the UK

