



Helping to protect lives globally

JoBird®

BUILT BY THE BEST TO WITHSTAND THE WORST.

Product data sheet

RS450PF Pumping and Flooding Locker



Typical use:

For the storage of Fire Equipment. This cabinet is used to store pumping and flooding equipment (damage control) in Naval vessels and has a NATO part number. NSN 2090-99-176-8388

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The roller shutter door enables access in confined spaces. The AS shutters used have proved to be extremely durable over a very long period of time.

The cabinet can be customised with shelves and brackets.

Standard specification:

Dimensions (mm)

Height x width x depth: 2000 x 1090 x 450

Aperture: 1530H x 902W

Internal depth: 396

Weight Kg: 35Kg

Material specification:

Colour: Blue RAL5002

Material: Lloyds approved composites with UV stabilised gelcoat

Class 1 fire retardant composites

Lettering: "PUMPING AND FLOODING LOCKER" 50mm white

Roller Shutter: Extreme Environment Roller Shutter

Optional Extras:

Other RAL colours



Manufactured in the UK

