



## Foam Wheeled Unit

### 45ltr Foam Fire Extinguisher

Product Code: FST2-045-000


The Aqueous Film Forming Foam (AFFF) additive is a blend of perfluorinated and hydrocarbon surfactants. It enables the formation of an aqueous film capable of spreading on the surface of burning fuels, which prevents vapour production and seals the surface from oxygen.

AFFF will extinguish class A fires and class B fires.

- CE marked in accordance with the PED
- Manufactured in accordance with and tested to BS1866
- Wheel marked in accordance with the MED
- Colour coded screen
- Manufactured in the UK
- Reliability
- Designed for long service in harsh conditions



Technical Specification								
Capacity (litres)	Fire rating	Temp Range	Operating pressure (bar) @ 20° C	Discharge duration (secs)	Discharge range (mtr)	Width (mm)	Depth (mm)	Height (mm)
45	11B	+5°C to +60°C	11.5	60	14	510	610	980



FlameSkill Ltd  
1 Morton Peto Estate  
Great Yarmouth  
Norfolk  
NR31 0LT  
Tel: 01493 440464  
Email: [admin@flameskill.co.uk](mailto:admin@flameskill.co.uk)  
Web: [www.flameskill.co.uk](http://www.flameskill.co.uk)