

ABC Powder Wheeled Extinguisher Unit

ABC Powder Wheeled Extinguisher

ABC powder is a combination of Mono-ammonium phosphate and ammonium sulphate. The extinguishing powder interferes with the chemical reactions that take place in the combustion zone, thus the flame ceases to exist. The powder also has a low melting point and on application the particles fuse and swell to form a barrier which excludes oxygen and completes the extinguishing process and prevents re-ignition.

The powder is non conductive and may be used in the presence of an electrical current.

ABC powder will extinguish class A (carbonaceous) fires, class B (flammable liquid) fires and class C (flammable gas) fires.

- CE marked in accordance with the PED
- Manufactured in accordance with and tested to BS1866
- Wheel marked in accordance with the MED
- Colour coded screen
- Manufactured in the UK
- Reliability
- Designed for long service in harsh conditions

THE ETHICUTE AND THE PROPERTY OF THE PROPERTY	
EST6_100_000	EST6_120_000

Model Ref	FST6-050-000	FST6-060-000	FST6-100-000	FST6-120-000
Capacity	50kg	60kg	100kg	120kg
Fire rating	11B	-	-	-
Operating pressure	11.5 bar at 20°C	11.5 bar at 20°C	14.5 bar at 20°C	14.5 bar at 20°C
Operating temperature	-30°C to +60°C	-30°C to +60°C	-30°C to +60°C	-30°C to +60°C
Height	980mm	980mm	1230mm	1230mm
Diameter	610mm	610mm	770mm	770mm
Filled weight (approx)	94kg	104kg	198kg	218kg



50kg MED approved only

FlameSkill Ltd
1 Morton Peto Estate
Great Yarmouth
Norfolk
NR31 OLT
Tel: 01493 440464
Email: admin@flameskill.co.uk
Web: www.flameskill.co.uk