




Foam Fire Extinguishers, Stored Pressure

Foam Fire Extinguishers

- Using the latest leading technology in manufacture all extinguishers are drawn cans
- High quality plated brass body valve
- 1ltr extinguisher complete with wire bracket and quick release strap to meet transport requirements
- 2ltr extinguisher fitted with fixed spray nozzle and wire bracket
- 6ltr and 9ltr extinguishers supplied with flexible hose and spray nozzle and durable plastic skirt
- Clear screen printed operating instructions for visibility and legibility
- Meets the di-electric test of 35K volts
- Reduced foam concentrate filling at 1.5%



Model Ref	FS02-015-000	FS02-025-000	FS02-065-000	FS02-095-000
Capacity	1ltr	2ltr	6ltr	9ltr
Fire rating	5A 21B	5A 55B	13A 144B	21A 183B
Operating pressure	12 bar at 20°C	12 bar at 20°C	12 bar at 20°C	12 bar at 20°C
Operating temperature	+5°C to +60°C	+5°C to +60°C	+5°C to +60°C	+5°C to +60°C
Height	365mm	420mm	540mm	610mm
Diameter	85mm	110mm	162mm	182mm
Filled weight (approx)	2.6kg	3.8kg	10kg	14kg



FlameSkill Ltd
 1 Morton Peto Estate
 Great Yarmouth
 Norfolk
 NR31 0LT
 Tel: 01493 440464
 Email: admin@flameskill.co.uk
 Web: www.flameskill.co.uk